



Product Code:
DEPT098

FEATURES

- 5.5L Big water tank
- Humidity setting(20%-90%)
- Water full alarm
- Universal casters, easy to move
- Intelligent defrosting
- Outage memory
- 0-24hr timer
- Washable air filter
- Water pump is optional with extra cost
- Best compressor from GMCC
- Whole copper pipe for the condenser & evaporator (high efficiency)
- Durable galvanized plate with coating surface (water-proof, rust-proof)
- Hot gas system ensure the dehumidifying capacity under low temperature (optional)

SPECIFICATIONS

Dehumidifying Capacity	70Pints/Day @80°F, 60%RH / 28.7L/Day (27°C, 60%RH)
Dehumidifying Capacity	110Pints/Day @86°F, 80%RH / 51L/Day (30°C, 80%RH)
Supply Voltage	115VAC, 60Hz / AC220V-240V/50Hz
Power Consumption & Current	635W, 6.0A @80°F, 60%RH / 545W, 2.7A (27°C, 60%RH)
Power Consumption & Current	728W, 6.75A @86°F, 80%RH / 650W, 3.1A (30°C, 80%RH)
Refrigerant	R410A/R290/R32
Air Circulation	450m ³ /h(265CFM)
Scope of Application	50~80m ² (538~861 sq. ft)
Body Dimension (D x W x H)	515 x 430 x 825mm(20.3" x 17" x 32.5")
Net Weight	36kg / 79.3lbs
Loading Quantity(20'/40'/40'HQ)	132/276/276