
Product data sheet





Cordless Rotary Hammer BITURBO with SDS max

GBH 18V-45 C



Cordless freedom with corded performance – the heavyduty all-rounder for concrete drilling and chiselling up to 45

The most important data

Battery voltage	18.0 V
Impact energy (according to EPTA 05/2016)	12.5 J
Drilling dia. in concrete with hammer drill bits	12 – 45 mm

Part Number 0 611 913 072

Technical data

Technical data

Impact energy (according to EPTA 05/2016)	12.5 J
Impact rate at rated speed	0 - 2,740 bpm
Rated speed	0 – 300 rpm
Battery voltage	18.0 V
Weight excl. battery	8 kg
Tool holder	SDS max
Packaging dimensions (width x length x height)	411 x 619 x 149 mm
Battery capacity	12 Ah
Weight incl. battery	9.3 kg
Drilling range	
Drilling dia. in concrete with hammer drill bits	12 – 45 mm
Opt. app. range in concrete with hammer drill bits	20 – 40 mm

Noise/vibration information

Hammer drilling in concrete

Vibration emission value ah	12.3 m/s ²
Uncertainty K	1.5 m/s ²
Chiselling in concrete	
Vibration emission value ah	7.3 m/s ²
Uncertainty K	1.5 m/s ²

Invented for life

Product data sheet

Power tools for trade & industry

Advantages:

- Cordless freedom with corded performance thanks to BITURBO Brushless technology
- Lighter than comparable corded products thanks to a highly optimized drive train, even with attached ProCORE18V 12.0Ah battery
- KickBack Control for reduced hazard of sudden tool reactions and Soft Start EPC & ASC for a comfortable and precise work process











